# Alliance Specialty Products High Performance Polymers

# **Material Safety Data Sheet**

**Product Name:** ASP 321 Pigmented Hardener HMIS CODES: H F R P

**Product Code: 321PIC Part B** 3 1 0 B

## **Section 1: Manufacturer Identification**

Manufacturer's Name: Alliance Specialty Products

Address: 2500 Sherwood Avenue

Charlotte, NC 28207

Phone: (704) 342-1977 Date Last Reviewed: 06/19/08

Fax (704) 342-1978 Prepared By: M. Swofford

> **CHEMICAL EMERGENCY CALL:** 1-800-535-5053

# **Section 2: Composition**

Ingredient	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
Polyetheramine	9046-10-0	N/E	N/E	N/E	>40%
Deta	111-40-0	N/E	N/E	N/E	<15%
Tris-2,4,6 (Dimethylaminomethyl) Phenol	90-72-2	N/E	N/E	N/E	>25%
Para-Nonylphenol	84852-15-3	N/E	N/E	N/E	<15%

#### **Section 3: Physical and Chemical Properties Section 4: Fire-Fighting Measures**

Boiling Point: Above 212°F		Combustible liquid OSHA Class III A			
Vapor Pressure:	Less than 1 mm Hg at 100°F	Explosive limits not determined			
Vapor Density:	Approximately 3.5	Flash Point:	208°F		
Solubility in	Very Slight	Extinguishing	Foam, dry chemical CO2		
Water:	-	Media:			
Specific Gravity:	~0.97	Special	Decomposition or products of		
Appearance:	Pale yellow liquid	Procedures:	combustion may be toxic. Use self		
Odor:	Ammoniacal odor		contained breathing equipment		
			and face shield.		
		Unusual	Downwind Personnel must be		
		Hazards:	evacuated. Burning produces toxic		
			fumes.		

# **Alliance Specialty Products**

High Performance Polymers

# **Material Safety Data Sheet**

## **Section 5: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Excessive heat or open flam

Material to Avoid: Organic acids, mineral acids, oxidizing agents, hydroxyl compounds.

Hazardous CO, CO2, oxides of nitrogen, aldehydes; nitrogen oxides may react with water

Decomposition or

vapor to form corrosive nitric acid.

Byproducts:

Hazardous Will not occur

Polymerization:

#### **Section 6: Hazards Identification**

Eyes: Causes eye burns. May cause blindness.

Skin: Harmful in contact with skin. May cause skin burns. Symptoms of overexposure may be

headache, dizziness, tiredness, nausea and vomiting.

Inhalation: Inhalation of aerosol may cause irritation to the upper respiratory tract. Can cause sever

respiratory tract burns.

Ingestion: Harmful if swallowed. If ingested, may cause sever burns to the mouth and throat, as well

as danger of perforation of the esophagus and the stomach.

#### **Section 7: First Aid Measures**

Eyes: Flush at once with potable water for at least 15 minutes and consult a physician.

Skin: Remove contaminated clothes immediately. Wash with soap and warm water for at least

15 minutes. Cover wound with sterile dressing.

Inhalation: Remove to fresh air. Administer oxygen if breathing is difficult.

Ingestion: Prevent aspiration of vomit. Turn victims head to the side. Seek immediate medical

assistance

#### **Section 8: Release Measures**

Steps to be Taken in Wear respirator and protective clothing. Shut off the leak at the source.

# **Alliance Specialty Products**

High Performance Polymers

# **Material Safety Data Sheet**

Event Material is Remove excess with vacuum truck, take up the remainder with an Released or Spilled: absorbent material such as clay, and place in disposal containers. Flush

area with water to remove residue.

## **Section 9: Waste Disposal**

Dispose of material in a waste disposal site in accordance with local, state, and federal law.

## **Section 10: Handling and Storage**

Precautions to Store in a cool, dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Mixed materials contain the

Handling and aggregate hazards of all the components, therefore, read the MSDS of all the

Storage: components prior to using the material. Properly label all containers.

Other Avoid skin contact. Avoid breathing vapors generated from the material. Observe Precautions: conditions of good general hygiene and safe working practices. Contaminated leather

articles can not be cleaned and must be discarded if contaminated with this product.

Wash all contaminated clothing prior to reuse.

## **Section 11: Exposure Controls**

Respiratory Protection: Not required for properly ventilated areas.

Ventilation: Exhaust ventilation sufficient to keep airborne concentrations of HDI below

their TLV and MGL maximum. Refer to Patty's Industrial Hygiene and Toxicology-Volume 1 Chapter 17 and Volume 3 Chapter 3 for details

Protective Gloves: Impervious gloves- neoprene or rubber.

Eye Protection: Splash goggles or glasses with side shields. Do not wear contact lenses when

using this product.

Other Protective Wear body covering clothing and other coverings as necessary such as an apron

Clothing or and appropriate footwear to avoid contact with the material.

Equipment:

Work Hygienic Observe good general hygienic practices.

Practices:

## **Section 12: Disclaimer**

The information contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.